[OEUNF-100]

Ultra Narrow Linewidth Passband FBG Filter

Features:

- All-fiber based structure
- TEM₀₀ beam profile
- Ultra-narrow linewidth
- Custom wavelength
- SM or PM-fibers

Applications:

- Spectroscopy
- Biomedical imaging
- Remote sensing
- Non-linear optics
- Telecommunications
- Quantum optics

Product description:

The OEUNF-100 Ultra Narrow Linewidth Filters based on Fiber Bragg Grating are cutting-edge optical components designed to provide exceptional wavelength selectivity with high transmission efficiency. O/E Lands' filters feature extremely narrow bandwidths, allowing them to isolate specific wavelengths with unparalleled precision, making them ideal for applications such as spectroscopy, laser systems, and telecommunications. With their superior performance in rejecting unwanted spectral noise, they are crucial for high-resolution systems that require precise control over the transmitted wavelength. O/E Lands' Ultra Narrow Linewidth Filters are engineered for reliability, durability, and optimal performance in demanding environments, delivering consistent results across a wide range of applications.

Product specifications:

Parameter	Unit	Value			
Туре		Ultra Narrow Linewidth FBG Filter			
Wavelength	nm	1030; 1060; 1310; 1550; 2000			
Operation mode		CW / Pulse			
FWHM Bandwidth (Passband)	pm	>5			
Isolation*	dB	> 30			
Insertion loss	dB	2 - 3			
Tuning range (optional)	pm	± 200			
Fiber type	·	SM; PM			

^{*}Higher isolation is available on request.

Ordering number for OEUBG-100:

Model	CWL (nm)	B (pm)	R (%)	Connector		Fiber Length		
OEUNF-100-CWL-B-R-C-FL	Center Wavelength	FWHM bandwidth	Reflectivity	FC/PC	C1	Default: 1 m		
				FC/APC	C2	Custom: specify value		
				SC/PC	C3			
				SC/APC	C4			
				LC/PC	C5			
				LC/APC	C6			
Example:	OEUNF-100-1550-10-95-C2-1							