

1x2 980/1550nm Fused PM Fiber WDM

Features of our WDM:

- Low excess Loss
- High Isolation Ratio
- High Power Handling
- Telcordia Compliant Test

Applications for our WDM:

- PM Fiber EDFA
- Monitoring in Coherent System

Specifications:

Specifications			980/1550nm	
Parameter		Unit	Premium	A grade
Pump Channel		nm	980+/-10	
Insertion Loss	Max.	dB	0.3	0.4
Isolation @1528 to 1565nm	Min.	dB	20	18
Signal Channel		nm	1528 to 1565	
Insertion Loss	Max.	dB	0.5	0.7
Isolation @980+/-10nm	Min.	dB	20	18
Operating Temperature		°C	0 to +70	
Storage Temperature		°C	-40 to +85	
Package Type		mm	S7	Diam. 3x60 for bare fiber

Ordering information:

- Wavelength: 980/1550nm
- Structure: 1x2
- Grade: Premium, A Grade
- Fiber type: Panda Fiber
- Pigtail: 250um bare fiber
- Fiber length: 0.5m, 1.0m



- Connector: none

We have unbeatable price for this product.

- Price is updating, please make a request for our most recent price by calling (514) 334-4588 or by emailing sales2@o-eland.com