

1x2 (2x2) Compact Single Mode Narrowband Splitter

Features of our splitter:

- Low PDL
- Low Insertion loss
- High Directivity
- Stable and Reliable
- Very Compact size

Applications for our splitter:

- Optical Communications System
- Optical Testing System
- Optical Fiber Sensor
- Optical Power Distributor

Specifications:

Specification				
Parameter		Unit	Premium	A grade
Port Configuration			1x2 or 2x2	
Bandwidth		nm	+/-10	
Insertion Loss	Max.	dB	3.4	3.7
Excess loss	Typ.	dB	0.1	0.15
Uniformity	Max.	dB	0.6	1.0
PDL	Max.	dB	0.1	0.15
Return Loss *	Min.	dB	50	
Operating Temperature		°C	-40 to +85	
Storage Temperature		°C	-50 to +85	
Package Type		mm	S2	Diam. 3x25.4: for bare fiber
			S4	Diam. 3x35: for 0.9mm loose tube

* >60dB on request for 1x2 structure

Splitting Ratio and Insertion Loss Conversion Table				
Splitting Ratio	Maximum Insertion Loss (dB)			
	Premium		A Grade	
Output Port	Output	Output Port	Output Port	Output Port 2

	Port 1	2	1	
50:50	3.4	3.4	3.7	3.7
60:40	2.5	4.4	2.8	4.8
70:30	1.8	5.6	2.0	6.1
80:20	1.1	7.4	1.3	8.0
90:10	0.6	10.8	0.8	12
95:5	0.4	14.6	0.5	18.4
96:4	0.35	16.0	0.45	19.0
97:3	0.3	17.5	0.4	19.5
98:2	0.25	19.0	0.35	20.0
99:1	0.2	21.5	0.3	22.0
99.5:0.5	0.2	23.0	0.3	24.0

Ordering Information:

- Wavelength: 1625, 1590, 1570, 1550, 1480, 1475, 1310
- Structure: 1x2, 2x2
- Splitting Ratio: 99.5:0.5, 99:1, 98:2, 97:3, 96:4, 95:5, 90:10, 80:20, 70:30, 60:40, 50:50
- Grade: Premium (P, A grade)
- Fiber type: SMF-28
- Pigtail: 250um bare fiber, 0.9mm loose tube
- Fiber length: 0.5m, 1.0m, 1.5m, 2.0m
- Connector: none, FC/PC, FC/APC, ST, customer's request

We have unbeatable price for this product.

- Price is updating, please make a request for our most recent price by calling (514) 334-4588 or by emailing sales2@o-eland.com